


8 7 6 5 4 3 2 1

SPECIFICATION CONTROL DRAWING



D

C

B

NOTES

1) D6021-XXX CROSSTUBE

LENGTH

WHERE XXX IS LENGTH IN INCHES
EG. 125" LONG TUBE: D6021-125

2) MATERIAL: 17-4PH H1100 SEAMLESS STAINLESS STEEL TUBE PER ASTM A564

MIN. ULTIMATE TENSILE STRENGTH = 140 ksi

MIN. YIELD TENSILE STRENGTH = 115 ksi

3) TOLERANCES ARE PER ASTM A519 AS FOLLOWS:

O.D.: +0.007/-0.000

I.D.: +0.000/-0.007

LENGTH: XXX +0.188/-0.000

STRAIGHTNESS: 0.010" DEVIATION / 12" LENGTH

4) ALL DIMENSIONS ARE IN INCHES

5) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE.

A

PRELIMINARY ISSUE

Rev. PAI 12.05.04

PAI	NEW ISSUE	CP	12.05.04
REV.	DESCRIPTION	BY	DATE
DESIGN	PAI	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	PAI		
CHECKED		DRAWING NO.	REV. PAI
MFG. APPR.		D6021	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		CROSSTUBE MATERIAL	NTS
DATE	12.05.04	COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	